

Kwikflex® NMLT Straight Conduit Connectors

Kwikflex™ nonmetallic liquidtight flexible (NMLT) conduit and fittings offer superior flexibility and corrosion resistance for protecting electrical wiring and connections to commercial and residential pool and spa motors, air conditioners, pumps and outdoor lighting.

Approved for use in dry, damp or wet locations, Kwikflex™ provides a positive, waterproof seal and easy, screw-together connectivity in indoor/outdoor, exposed or concealed environments. Kwikflex NMLT is UL listed and permitted for use by the NEC (Article 356) in exposed and concealed locations for the protection of conductors where a degree of flexibility is required.

FEATURES & BENEFITS

- Available 3/8" through 2"
- All nylon construction resists salt water, weak acids, gasoline, alcohol, oil, grease & common solents
- No disassembly required. Instead, the installer simply pushes the conduit or tubing onto the ferrule, tightening the domed sealing nut. The completed assembly can then be secured in the chassis by the locknut (or first secure the connector into an NPT threaded hole)
- No threading of the conduit or tubing required to install, eliminating the possibility of cutting the conduit & creating leak paths
- Standard color - Gray
- Complete conduit/connector system is reusable. Conduit will not wind tight onto the connector during assembly & can be easily removed by pulling while turning in a clockwise direction
- Suitable for indoor/outdoor use; for original equipment manufacturers or field installers
- Lower installed cost
- Molded of type nylon 6. Flammability classification 94V-2; temperature index 125°C
- "O" Ring & steel locknut included

STANDARDS



APPLICATIONS

- HVAC equipment
- Machine tools
- Marine equipment
- Motors & controls
- Printing equipment
- Pumps
- Refrigeration equipment
- Assemblies
- Wire hook-up

SPECIFICATIONS

Part No.	Product Code	Trade Size	K.O. Size	Std. Pkg	Weight / Pkg.	Part Dimensions (inches)		
						A	B	C
LTS03	065326	3/8"	1/2"	25/100	5	2.000	0.540	1.400
LTS10	065327	1/2"	1/2"	25/100	5	2.000	0.540	1.400
LTS15	065330	3/4"	3/4"	10/100	7	2.200	0.635	1.700
LTS20	065332	1"	1"	5/50	7	2.280	0.740	2.000
LTS25	065334	1-1/4"	1-1/4"	5/25	5	2.440	0.760	2.400
LTS30	065337	1-1/2"	1-1/2"	2/10	3	2.700	0.800	2.670
LTS35	065340	2"	2"	2/10	4	2.990	0.850	3.280

Available in Black upon request

