

NEW PRODUCT SHOWCASE

The **NEW** Standard in Water Service Tubing

Gold901™ is a lightweight, easy to install, 250 psi rated water service tubing that can be used on both the municipal and private-side of a project.

Gold901 is manufactured to Copper Tube Size (CTS) from High-Density Polyethylene (HDPE) and is third-party certified and listed to AWWA C901, CSA B137.1 and NSF 61.

Gold901 is conveniently available in both coils and reels and is available in 3/4" to 2".



Features

Non-corroding

Resistant to corrosive soils, aggressive water, stray electrical currents and moist environments

Lightweight

A 200 foot coil of 3/4" Gold901 weighs 20 lbs

Sequential Markings

Every 2 or 5 feet

Superior Flow

Hazen Williams C-Factor = 150

High Pressure

Rated at 250 psi at 73°F (1,725 kPa at 23°C)

Standards



B137.1



NSF-61



AWWA C901



Product Selection Chart

Nominal Pipe Size inches	mm	Coil Length feet	Product Code	O.D. Average (in)	I.D. Average (in)	Min. Radius of Bend (in)
3/4	20	100	121402	0.875	0.671	19
		200	121403			
		400	121404			
		500	121405			
		3000	121406			
1	25	100	121407	1.125	0.863	23
		150	121408			
		200	121409			
		300	121410			
		500	121411			
		1000	121412			
1-1/4	32	100	121414	1.375	1.055	30
		300	121415			
		100	121416			
1-1/2	40	250	121417	1.625	1.245	34
		400	121418			
		1000	121419			
		100	121420			
2	50	200	121421	2.125	1.629	44
		500	121422			

NOTE: Custom coil and reel sizes may be available upon request.